



# Lone Star Trencher Parts, LLC.

(Woman Owned Small Business)

10157 IH 35 N. Frontage Rd. Ste. A ♦ San Antonio, TX 78233

PH: (210) 492-5960 ♦ FAX: (210) 492-3043

## Hunting - Drill stem specifications and dimensional information.

	Part Number	Tube Diameter (in) Wall (in)	Tube Diameter (mm) Wall (mm)	Connection (Thread Size)	Weight lb (kg)	Length ft (m)	Bend Radius ft (m)	%Slope per rod	Torque Rating ft-lb (Nm)
<b>HIWS1</b>	HI216490	1.660 / .191	42.2 / 4.9	200	21 (9.5)	5 (1.5)	95.5 (29.1)	5.2%	1,500 (2034)
	HI216492	1.660 / .191	42.2 / 4.9	200	26 (11.8)	6 (1.8)	95.5 (29.1)	6.2%	1,500 (2034)
	HI230993	1.900 / .240	48.3 / 6.1	250	55 (24.9)	10 (3.0)	98.7 (30.1)	10.2%	2,300 (3118)
	HI221628	2.063 / .260	52.4 / 6.6	400	62 (28.1)	10 (3.0)	102 (31.1)	9.8%	2,700 (3661)
	HI222276	2.375 / .254	60.3 / 6.5	600	76 (34.5)	10 (3.0)	108 (32.9)	9.3%	4,200 (5694)
	HI296309599*	2.375 / .295	60.3 / 7.5	650	84 (38.1)	10 (3.0)	108 (32.9)	9.3%	5,500 (7457)
	HI296312531*	2.375 / .295	60.3 / 7.5	650	115 (52)	15 (4.6)	108 (32.9)	13.9%	5,500 (7457)
	HI296309521	2.625 / .400	66.7 / 10.2	700	117 (53)	10 (3.0)	145 (44.2)	6.9%	6,000 (8135)
	HI296309522	2.625 / .400	66.7 / 10.2	700	165 (75)	15 (4.6)	145 (44.2)	10.4%	6,000 (8135)
	HI222451*	2.875 / .392	73.0 / 10.0	900	120 (54)	10 (3.0)	169 (51.5)	5.8%	9,300 (12609)
	HI222452	2.875 / .392	73.0 / 10.1	900	180 (82)	15 (4.6)	169 (51.5)	8.7%	9,300 (12609)
	HI222454	3.500 / .449	88.9 / 10.4	800	250 (113)	15 (4.6)	197 (60.1)	7.5%	12,000 (16270)
	HI296337977	3.500 / .476	88.9 / 12.1	1000	265 (120)	15 (4.6)	197 (60.1)	7.5%	15,000 (20337)
	HI296309520	3.500 / .476	88.9 / 12.2	1000	351 (159)	20 (6.1)	197 (60.1)	10.2%	15,000 (20337)
<b>HXT™</b>	HI281600*	2.063 / .260	52.4 / 6.6	402	63 (28.6)	10 (3.0)	102 (31.1)	9.8%	3,300 (4474)
	HI294566	2.375 / .295	60.3 / 7.5	602	81 (36.7)	10 (3.0)	108 (32.9)	9.3%	5,000 (6779)
	HI284153	2.375 / .295	60.3 / 7.6	602	115 (52)	15 (4.6)	108 (32.9)	13.9%	5,000 (6779)
	HI294642	2.625 / .400	66.7 / 10.2	602	160 (73)	15 (4.6)	145 (44.2)	10.4%	5,000 (6779)
	HI276305*	2.625 / .400	66.7 / 10.2	702	164 (74)	14.8 (4.5)	145 (44.2)	10.0%	7,000 (9491)
	HI276307*	2.875 / .440	73.0 / 11.2	902	198 (90)	15 (4.6)	169 (51.5)	8.9%	13,000 (17626)
	HI350802015	3.500 / .449	88.9 / 10.4	802	260 (118)	15 (4.6)	197 (60.1)	10.1%	18,000 (24405)
	HI276376	3.500 / .449	88.9 / 10.4	802	327 (148)	20 (6.1)	197 (60.1)	7.5%	18,000 (24405)
<b>Ditch Witch®</b>	355-1106	2.060 / .295	52.3 / 7.5	1.94-4	68 (30.1)	10 (3.0)	109 (32.2)	9.2%	2,000 (2980)
	355-1244	2.375 / .300	60.3 / 7.6	2.11-4	81 (36.7)	9.8 (3.0)	123 (37.5)	8.0%	4,000 (5420)
	359-1211	2.835 / .313	72.0 / 8.0	2.10-4	140 (63.5)	15 (4.6)	146 (44.5)	10.3%	5,500 (7457)
<b>Lined</b>	355-1106L	2.060 / .295	52.3 / 7.5	1.94-4	73 (33.1)	10 (3.0)	109 (32.2)	9.2%	2,000 (2980)
	355-1244L	2.375 / .300	60.3 / 7.6	2.11-4	86 (39.0)	9.8 (3.0)	123 (37.5)	8.0%	4,000 (5420)
<b>Advantage</b>	A216492	1.660 / .191	42.2 / 4.9	200	26 (11.8)	6 (1.8)	99.0 (30.2)	6.1%	1,500 (2034)
	A221628	2.063 / .260	52.4 / 6.6	400	62 (28.1)	10 (3.0)	107 (32.6)	9.4%	2,700 (3661)
	A222276	2.375 / .254	60.3 / 6.5	600	76 (34.5)	10 (3.0)	123 (37.5)	8.1%	4,200 (5694)
	A355-1106	2.060 / .295	52.3 / 7.5	1.94-4	68 (30.8)	10 (3.0)	107 (32.6)	9.4%	2200 (2983)
	A355-1244	2.375 / .300	60.3 / 7.6	2.11-4	81 (36.7)	9.8 (3.0)	123 (37.5)	8.0%	4,000 (5420)
<b>AT</b>	355-1050-500	3.630 / .313	92.2 / 8.0	3.44-4	302 (137)	14.1 (4.3)	205 (62.5)	6.9%	12,000 (16270)